

KEN WASHER DISINFECTOR IQ6

# Intelligent Quality

- The Future of Efficient Disinfection

- ✓ Easy to use
- ✓ Easy to service
- ✓ Easy to choose

The IQ series is a modular built range that meets all relevant standards such as ISO 15883, UL to name a few.

The elegant design provides a smooth surface in tempered glass that is easy to clean. The IQ6 has downward sliding doors that allows for manual loading, or the use of a unique automatic loading that provides high flexibility and uses very little space.

The IQ6 is easy to operate by touch panel with swipe function, showing all relevant information of the program needed by the operators.

IQ6 has the lowest energy and water consumption in the market, to keep operating costs at a minimum and contribute to a clean environment.

IQ6 comes with a wide range of racks and modules and holds up to 18 DIN baskets.

All data from the IQ6 are fully exchangeable with common computer systems.



# HEALTHCARE



A wide range of racks, modules and even special demands equipment can be provided to solve your disinfection needs.

### Advantages:

#### Environment

- Low energy costs
- Low noise level
- Low chemical usage
- Very low water consumption

#### Technology

- RFID recognition
- Robotic loading / unloading
- Service access from the front

#### Hygiene safety

- EN 62366 tested
- EN ISO 15883-1-2-5

#### Validation of all processes

- Open programs structure
- Full process validation
- Exchange of data

Description	Values
<b>Outer dimensions</b>	H: 1985 x W: 820 x D: 936 mm
<b>Operative chamber dimensions</b>	H: 690 x W: 705 x D: 850 mm
<b>Weight excl./incl. packaging</b>	340 / 405 kg
<b>Operative volume, wash chamber</b>	413 L
<b>Total volume, wash chamber</b>	492 L
<b>Capacity DIN-baskets 480x250x50mm</b>	18
<b>Cycle time, standard</b>	35-45 min. (fast cycle machine <30 min.)
<b>Exhaust connections</b>	ø100 mm 385 m3 per hour
<b>Water connections</b>	2 x 3/4 (3rd is optional)
<b>Cold water</b>	200-800kPa, ≥15L7min, 5-30°, 0-3° dH
<b>Hot water</b>	200-800kPa, ≥15L7min, 30-70°, 0-3° dH
<b>Demineralized /RO water</b>	200-800kPa, ≥15L7min, 5-70° C - option
<b>Washing / Drying</b>	<56.5 dB(A) / < 60.5 dB(A)
<b>Water consumption per phase</b>	Approx. 22-25 L (standard 5-level rack)
<b>Power supply options</b>	3x200-480 + N +PE 50/60 Hz 14-26 kW
<b>Connected load</b>	Max 26 kW, 40A
<b>Programs available</b>	10 standard + 30 optional
<b>Drain</b>	ø50 mm



LTE Scientific Ltd  
Greenbridge Lane, Greenfield, Oldham, OL3 7EN

E-mail: [info@lte-scientific.co.uk](mailto:info@lte-scientific.co.uk)  
Web: [www.lte-scientific.co.uk](http://www.lte-scientific.co.uk)  
Tel: +44 (0)1457 876 221

Clean, Lean & Green