

}•šr ((š]À U }u%œ Z v•]À μš} o A
]v•šœμu vš•U •%o](] ooÇ P œ š} šZ
 À š œ]v œÇ u œI š•X

RELIABILITY
 & μ oo Ç } u %o o] v š A] š Z oo
 μ œ œ v š] œ š] À •

SECURITY
 Automatic closing with
 double safety } I

^ _ C > ^ ^ h d K >

s h h D W h D W
 W œ } À] • } %o š] u
 œ u } À o (} œ %
 %o v š œ š] } v

LOW CONSUMPTION
 D] v] water
 } v • μ u %o š] } v %o œ



STERILIZATION CHAMBER
 CAPACITY
60lt

AUTOMATIC WATER
 LOADING AND DISCHARGE

BUILT-IN PRINTER

E TOP
 / o (} œ œ
 • %o } v • š œ

TRACEABILITY
 SD ard • œ } š
 • š v œ

TECHNICAL DATA

Power supply:	230V- 50/60Hz Monophase 15A
Chamber volume:	60lt in stainless steel (ø350x606mm)
Load:	9Kg
Weight	62Kg
Dimensions without cabinet:	615x730x 750 mm (WxDxH)
Dimensions with cabinet	615x730x 1500 mm (WxD)

Produced in accordance with the current directives and standards.

K W d / K E > y
 & o } } œ ^ š v] v
 Z K t š œ ^ Ç •

(, 4 %) IS) A) PROGRESSIVE) COMPAN
 RIGHT) TO) ALTER) THE) SPECIFICA
 WITHOUT) NOTICE) % / %)))) - % \$

> d ^] v š] (] > š U ' œ v œ] P > v U ' œ v (] o U K o Z u U
 d W = ð ð - i • i ð ñ W ð ð ð] i ð i s] (] X W X X o š r •] v š] (] X } X μ I

